



SSR MOTORSPORTS

SSR Motorsports, since 2002 we have been building the products that open up the world of riding.

What sets SSR apart is our focus on bringing cutting edge design, superior engineering, and value for money to the smaller displacement market. We believe that every enthusiast should be able to afford a brand new powersport product from a comprehensive dealer network, with the backing of an expansive distribution center stocked with readily available replacement parts.

Thank you for your interest, whether you are looking for a vehicle for yourself or a vehicle to share the riding experience with your family; whether your interest is ribbons of asphalt or your favorite stretch of dirt road; our knowledgeable and experienced staff is on hand to provide you with the customer service and technical support you need.

SSR OFF-ROAD MODELS



*Also Available with 17 | 17 Street Tires

XF250

Dual Sport Bike
249 cc | 4 Stroke
328 lbs. | 81" x 30.5" x 44"

ENGINE	
Bore And Stroke	72mm x 61.2mm
Carburetor	26mm
Max Output	18.1 hp @ 7000 rpm
Ignition	CDI
Start Mode	Electric Start
Transmission	5 Speed Manual, 1-Down, 4-Up

CHASSIS	
Front Suspension	Adjustable Fork, Inverted
Rear Suspension	Coil Spring Shock
Brake	Disc Disc
Tire*	4.60-18 5.10-17 (Dual Sport Tires)
Frame	Steel
Swingarm	Alluminum Alloy, Box Section

DIMENSIONS	
Wheelbase	57 inches
Seat Height	35 inches
Ground Clearance	8 inches

ENGINE	
Engine Type	Horizontal Type, Air Cooled
Max Output	11.1 hp @ 8000 rpm
Ignition	CDI
Start Mode	Electric Start
Transmission	Belt Drive + Chain Drive w/ CVT (F-N-R)

CHASSIS	
Front Suspension	Double A-arm
Rear Suspension	Swingarm
Brake	Disc Disc
Tire	21x7-10 22x10-10
Frame	Steel

DIMENSIONS	
Wheelbase	72 inches
Ground Clearance	7 inches
Fuel Tank	2.90 gallons
Weight Capacity	330 pounds
Cargo Bed	33" x 16" x 6"



SRU170RS

Youth UTV
168.9 cc | Black / Blue
540 lbs. | 98" x 48" x 60"



BUSINESS CARD



www.ssrmotorsports.com

SSR Motorsports

12825 Alondra Blvd. • Norwalk, CA 90650

Ph: (562) 926-2888 Fx: (562) 926-6999



Off-road Lineup



SX50-A

Base Model Pit Bike
50.53 cc | 2 Stroke
48.5 lbs. | 49" x 23" x 31"

ENGINE	
Bore And Stroke	44.02mm x 33.2mm
Carburetor	16mm
Max Output	2.4 hp @ 7000 rpm
Ignition	Coil
Start Mode	Pull Start
Transmission	Automatic
CHASSIS	
Front Suspension	Spring, Inverted
Rear Suspension	190.5mm Shock
Brake	Disc Disc
Tire	2.50-10 2.50-10
Frame	Steel
Swingarm	Steel, "Straight" Type
DIMENSIONS	
Wheelbase	36 inches
Seat Height	23 inches
Ground Clearance	8.5 inches



SR70C

Base Model Pit Bike
72 cc | 4 Stroke
113 lbs. | 53" x 24" x 31"

ENGINE	
Bore And Stroke	47mm x 41.4mm
Carburetor	16mm
Max Output	4.69 hp @ 7500 rpm
Ignition	CDI
Start Mode	Kick Start
Transmission	4-Down Semi-Automatic
CHASSIS	
Front Suspension	Hydraulic, Conventional
Rear Suspension	265mm Shock
Brake	Disc Disc
Tire	2.50-10 2.50-10
Frame	Double Bar Steel Frame
Swingarm	Steel, "Straight" Type
DIMENSIONS	
Wheelbase	43 inches
Seat Height	22.5 inches
Ground Clearance	6 inches



SR70AUTO

Base Model Pit Bike
72 cc | 4 Stroke
113 lbs. | 53" x 24" x 31"

ENGINE	
Bore And Stroke	47mm x 41.4mm
Carburetor	16mm
Max Output	4.69 hp @ 7500 rpm
Ignition	CDI
Start Mode	Electric Start
Transmission	Automatic
CHASSIS	
Front Suspension	Hydraulic, Conventional
Rear Suspension	255mm Shock
Brake	Disc Drum
Tire	2.50-10 2.50-10
Frame	Double Bar Steel Frame
Swingarm	Steel, "A" Type
DIMENSIONS	
Wheelbase	39 inches
Seat Height	21.5 inches
Ground Clearance	5 inches



SR110

Base Model Pit Bike
107 cc | 4 Stroke
122 lbs. | 59" x 29" x 40"

ENGINE	
Bore And Stroke	52.4mm x 49.5mm
Carburetor	16mm
Max Output	6.2 hp @ 7500 rpm
Ignition	CDI
Start Mode	Kick Start
Transmission	4-Up Manual
CHASSIS	
Front Suspension	Hydraulic, Conventional
Rear Suspension	265mm Shock
Brake	Disc Disc
Tire	2.75-12 3.00-10
Frame	Steel Back Bone
Swingarm	Steel, "Straight" Type
DIMENSIONS	
Wheelbase	42.5 inches
Seat Height	28 inches
Ground Clearance	10 inches



SR110SEMI

Base Model Pit Bike
107 cc | 4 Stroke
122 lbs. | 59" x 29" x 40"

ENGINE	
Bore And Stroke	52.4mm x 49.5mm
Carburetor	16mm
Max Output	6.2 hp @ 7500 rpm
Ignition	CDI
Start Mode	Kick Start
Transmission	4-Up Semi-Automatic
CHASSIS	
Front Suspension	Hydraulic, Conventional
Rear Suspension	265mm Shock
Brake	Disc Disc
Tire	2.75-12 3.00-10
Frame	Steel Back Bone
Swingarm	Steel, "Straight" Type
DIMENSIONS	
Wheelbase	42.5 inches
Seat Height	28 inches
Ground Clearance	10 inches



SR110DX

Deluxe Model Pit Bike
107 cc | 4 Stroke
122 lbs. | 59" x 29" x 40"

ENGINE	
Bore And Stroke	52.4mm x 49.5mm
Carburetor	16mm
Max Output	6.2 hp @ 7500 rpm
Ignition	CDI
Start Mode	Kick Start
Transmission	4-Up Manual
CHASSIS	
Front Suspension	Hydraulic, Conventional
Rear Suspension	265mm Shock
Brake	Disc Disc
Tire	2.75-12 3.00-10 (Anodized Alloy Rims)
Frame	Steel Back Bone
Swingarm	Steel, "Straight" Type
DIMENSIONS	
Wheelbase	42.5 inches
Seat Height	29 inches
Ground Clearance	10 inches



SR125

Base Model Pit Bike
124 cc | 4 Stroke
129 lbs. | 65" x 29" x 40"

ENGINE	
Bore And Stroke	54mm x 54mm
Carburetor	22mm
Max Output	7.3 hp @ 7500 rpm
Ignition	CDI
Start Mode	Kick Start
Transmission	4-Up Manual
CHASSIS	
Front Suspension	Hydraulic, Conventional
Rear Suspension	275mm Shock
Brake	Disc Disc
Tire	2.50-14 3.00-12
Frame	Double Bar Steel Frame
Swingarm	Steel, "Straight" Type
DIMENSIONS	
Wheelbase	47 inches
Seat Height	30 inches
Ground Clearance	10.5 inches



SR125SEMI

Base Model Pit Bike
124 cc | 4 Stroke
129 lbs. | 65" x 29" x 40"

ENGINE	
Bore And Stroke	54mm x 54mm
Carburetor	22mm
Max Output	7.3 hp @ 7500 rpm
Ignition	CDI
Start Mode	Kick Start
Transmission	4-Up Semi-Automatic
CHASSIS	
Front Suspension	Hydraulic, Conventional
Rear Suspension	275mm Shock
Brake	Disc Disc
Tire	2.50-14 3.00-12
Frame	Double Bar Steel Frame
Swingarm	Steel, "Straight" Type
DIMENSIONS	
Wheelbase	47 inches
Seat Height	30 inches
Ground Clearance	10.5 inches



SR125AUTO

Base Model Pit Bike
124 cc | 4 Stroke
129 lbs. | 65" x 29" x 40"

ENGINE	
Bore And Stroke	54mm x 54mm
Carburetor	22mm
Max Output	7.3 hp @ 7500 rpm
Ignition	CDI
Start Mode	Electric Start
Transmission	Automatic
CHASSIS	
Front Suspension	Hydraulic, Conventional
Rear Suspension	275mm Shock
Brake	Disc Disc
Tire	2.50-14 3.00-12
Frame	Double Bar Steel Frame
Swingarm	Steel, "Straight" Type
DIMENSIONS	
Wheelbase	47 inches
Seat Height	30 inches
Ground Clearance	10.5 inches



SR110TR

TR Series Pit Bike
107 cc | 4 Stroke
147 lbs. | 63.5" x 27" x 37"

ENGINE	
Bore And Stroke	52.4mm x 49.5mm
Carburetor	16mm, Mikuni
Max Output	7 hp @ 7500 rpm
Ignition	CDI
Start Mode	Kick Start
Transmission	4-Up Semi-Automatic
CHASSIS	
Front Suspension	R/C Adjustable Forks, Inverted
Rear Suspension	280mm Shock, 850 lbs.
Brake	Disc Disc
Tire	60/100-14 80/100-12
Frame	Double Bar Steel Frame w/ Sub-Frame
Swingarm	Steel, "Straight" Type
DIMENSIONS	
Wheelbase	44.5 inches
Seat Height	28.4 inches
Ground Clearance	10 inches



SR125TR

TR Series Pit Bike
124 cc | 4 Stroke
157 lbs. | 66" x 29.5" x 43"

ENGINE	
Bore And Stroke	54mm x 54mm
Carburetor	22mm, Mikuni
Max Output	8.5 hp @ 7500 rpm
Ignition	CDI
Start Mode	Kick Start
Transmission	4-Up Manual
CHASSIS	
Front Suspension	Hydraulic, Inverted (Black)
Rear Suspension	290mm Shock, 850 lbs.
Brake	Disc Disc
Tire	60/100-14 80/100-12
Frame	Double Bar Steel Frame w/ Sub-Frame
Swingarm	Steel, "Straight" Type
DIMENSIONS	
Wheelbase	48 inches
Seat Height	32 inches
Ground Clearance	12 inches



SR140TR

TR Series Pit Bike
140 cc | 4 Stroke
157 lbs. | 66" x 29.5" x 43"

ENGINE	
Bore And Stroke	55mm x 59mm
Carburetor	26mm, Mikuni
Max Output	12 hp @ 8500 rpm
Ignition	CDI
Start Mode	Kick Start
Transmission	4-Up Manual
CHASSIS	
Front Suspension	R/C Adjustable Forks, Inverted
Rear Suspension	290mm Adjustable Shock, 1000 lbs.
Brake	Disc Disc
Tire	60/100-14 80/100-12
Frame	Double Bar Steel Frame w/ Sub-Frame
Swingarm	Steel, "Straight" Type
DIMENSIONS	
Wheelbase	48 inches
Seat Height	32 inches
Ground Clearance	12 inches



SR170TR

TR Series Pit Bike
169 cc | 4 Stroke
157 lbs. | 66" x 29.5" x 43"

ENGINE	
Bore And Stroke	62mm x 56mm
Carburetor	26mm, Mikuni
Max Output	15.8 hp @ 9000 rpm
Ignition	CDI
Start Mode	Kick Start
Transmission	4-Up Manual
CHASSIS	
Front Suspension	R/C Adjustable Forks, Inverted
Rear Suspension	290mm Adjustable Shock, 1000 lbs.
Brake	Disc Disc
Tire	60/100-14 80/100-12
Frame	Double Bar Steel Frame w/ Sub-Frame
Swingarm	Steel, "Straight" Type
DIMENSIONS	
Wheelbase	48 inches
Seat Height	32 inches
Ground Clearance	12 inches



SR170TX

TX Series Pit Bike
169 cc | 4 Stroke
149 lbs. | 68" x 29.5" x 42"

ENGINE	
Bore And Stroke	62mm x 56mm
Carburetor	26mm, Mikuni
Max Output	15.8 hp @ 9000 rpm
Ignition	CDI
Start Mode	Kick Start
Transmission	4-Up Manual
CHASSIS	
Front Suspension	R/C Adjustable Forks, Inverted
Rear Suspension	275mm DNM R/C Adjustable Shock
Brake	Disc Disc
Tire	60/100-14 80/100-12 (Kenda Tires)
Frame	Chromoly Steel Frame w/ Sub-Frame
Swingarm	Aluminum Alloy, "Straight" Type
DIMENSIONS	
Wheelbase	48 inches
Seat Height	30.5 inches
Ground Clearance	10.5 inches



SR150

Mid-size Dirt Bike
150 cc | 4 Stroke
227 lbs. | 73.2" x 31" x 44"

ENGINE	
Bore And Stroke	62mm x 49.6mm
Carburetor	28mm
Max Output	13.4 hp @ 9000 rpm
Ignition	CDI
Start Mode	Electric / Kick Start
Transmission	5 Speed Manual, 1-Down, 4-Up
CHASSIS	
Front Suspension	Hydraulic, Inverted, 230mm Trvl.
Rear Suspension	450mm Adj. Shock, 180mm Trvl.
Brake	Disc Disc
Tire	70/100-17 90/100-14
Frame	Cast Steel w/ Formed Steel Tube
Swingarm	Steel - Box Section
DIMENSIONS	
Wheelbase	51.5 inches
Seat Height	33.5 inches
Ground Clearance	11 inches



SR189

Mid-size Dirt Bike
189 cc | 4 Stroke
236 lbs. | 74.4" x 31" x 45.7"

ENGINE	
Bore And Stroke	65.5mm x 56.2mm
Carburetor	30mm
Max Output	15.4 hp @ 8500 rpm
Ignition	CDI
Start Mode	Electric / Kick Start
Transmission	5 Speed Manual, 1-Down, 4-Up
CHASSIS	
Front Suspension	R/C Adjustable, Inverted, 255mm Trvl.
Rear Suspension	450mm Adj. Shock, 215mm Trvl.
Brake	Disc Disc
Tire	70/100-19 90/100-16
Frame	Cast Steel w/ Formed Steel Tube
Swingarm	Steel - Box Section
DIMENSIONS	
Wheelbase	52 inches
Seat Height	35 inches
Ground Clearance	12.4 inches



SR250S

Full-size Dirt Bike
249.6 cc | 4 Stroke
260 lbs. | 91" x 32.5" x 51"

ENGINE	
Bore And Stroke	77mm x 53.6mm
Carburetor	34mm
Max Output	25.8 hp @ 9000 rpm
Ignition	CDI
Start Mode	Electric / Kick Start
Transmission	5 Speed Manual, 1-Down, 4-Up
CHASSIS	
Front Suspension	R/C Adjustable, Inverted, 315mm Trvl.
Rear Suspension	P/R Adjustable Shock, 270mm Trvl.
Brake	Disc Disc
Tire	80/100-21 100/90-18
Frame	Aluminum Alloy
Swingarm	Aluminum Alloy, "Straight" Type
DIMENSIONS	
Wheelbase	59 inches
Seat Height	37.8 inches
Ground Clearance	12.2 inches



SR450S

Full-size Dirt Bike
449 cc | 4 Stroke
265 lbs. | 91" x 32.5" x 51"

ENGINE	
Bore And Stroke	96mm x 62.1mm
Carburetor	36mm
Max Output	43.5 hp @ 7500 rpm
Ignition	CDI
Start Mode	Electric / Kick Start
Transmission	5 Speed Manual, 1-Down, 4-Up
CHASSIS	
Front Suspension	R/C Adjustable, Inverted, 315mm Trvl.
Rear Suspension	P/R Adjustable Shock, 270mm Trvl.
Brake	Disc Disc
Tire	80/100-21 110/100-18 (CST Tires)
Frame	Aluminum Alloy
Swingarm	Aluminum Alloy, "Straight" Type
DIMENSIONS	
Wheelbase	59 inches
Seat Height	37.8 inches
Ground Clearance	12.2 inches